USIYEVICH, M.A., kand. ekon. nauk; VIDMAR, V.N., kand. ekon. nauk; STUPOV, A.D., kand. sel'khoz. nauk; STARODUBROVSKAYA, V.N., kand. ekon. nauk; STOROZHEV, V.I., kand.ist. nauk; RUDAKOV, Ye.V., kand. ekon. nauk; KIRANOV, P., prof.; KHORVAT, L. [Horvat, L.], kand. ekon. nauk; KROMM, K., doktor; FRUKK, Kh. [Frukk, H.], doktor; SHMIDT, V.[Schmidt, V.], prof., doktor; TEPIKHT, Ye.[Tepicht, E.], prof.; NIK, S. [Nic,S.], kand. ekon. nauk; DUMITRIY, D.[Dumitro, D.]; SVOBODA, K., kand. ekon. nauk; LEPNIKOVA, Ye., red.; KIRSANOVA, I., mladshiy red.; NOGINA, N., tekhn. red.

[Socialist reorganizations in the agriculture of the European people's democracies] Sotsialisticheskie preobrazovaniia v sel'skom khoziaistve evropeiskikh stran narodnoi demokratii. Moskva, Sotsekgiz, 1963. 334 p. (MIRA 16:7)

1. Akademiya nauk SSSR. Institut ekonomiki mirovoy sotsialisticheskoy sistemy.2. Institut ekonomiki mirovoy sotsialisticheskoy sistemy AN SSSR (for Usiyevich, Vidmar, Stupov, Starodubrovskaya, Storozhev, Rudakov).
(Europe, Eastern--Agriculture, Cooperative)

[illegible], I. F., [illegible], Vol., [illegible]; [illegible], S. V., [illegible].

Investigating the stability of [illegible] soil for cold rolling. Izv. vys. ucheb. zav.; [illegible], no. [illegible] '65. (MIRA 18:8)

FUZNOVICH, L.S.; PSHENNIKOV, V.I.; STOROZHEV, V.M.; MEDVEDEV, T.I.

Using natural sodium brine to cool industrial liquids. Prom. energ. 12 no.8:18 Ag '57. (MIRA 10:10)
(Soda industry) (Cooling)

SPOKOZHEV, V.N., inzh.

Stopping steam boilers with closed valves. Mekh. trans. 18 no.8:47 Ag '59. (MIRA 12:12)
(Boilers--Incrustations)

STOROZHEV, V.N., inzh.-mekhanik

Should the underwater part of Yenisey River steel ship hulls be painted. Rech.transp. 18 no.11:21-22 N '59. (MIRA 13:4)
(Yenisey River--Inland navigation) (Ships--Painting)

ACC NR: AR6019560 (N) SOURCE CODE: UR/0393/65/000/003/1013

AUTHOR: Storozhev, V. N.; Goleshchikhin, Yu. I.; Kolesnikova, K. P.

TITLE: Continuous use of lubricating oil in the M-50 engine

SOURCE: Ref. zh. Vodnyy transport, Abs. 1V87

REF SOURCE: Proizv.-tekhn. sb. Tekhn. upr. M-va rechn. flota RSFSR, no. 3 (47), 1965, 28-30

TOPIC TAGS: diesel engine, marine engine, engine reliability, lubricating oil, propulsion research facility

ABSTRACT: Experiments in the operation of the M-50 engine without changing the lubricating oil were conducted by the NIIVT [Novosibirsk Institute for Water Transportation Engineers]. MS-20 lubricating oil with additive TsIATIM-339 and fuel DS GOST 4749-49, was used. A table containing the comparative results of M-50 operation in the 1964 season is presented. Oil consumption is considerably lower when no oil change is made. No alkalis or water-soluble acids were found in the samples taken. Engines with the same remaining engine life were checked, with and without oil change, and it was shown that the degree of clogging in the oil bypasses with low temperature deposits of the products of oxidization polymerization was the same. There was no observed variation in the operation of the engines. [Translation of abstract]

SUB CODE: 21,11

Card 1/1 UDC: 621.431.74:621.892.096.1

KOMISSAROV, A.I., kand. tekhn. nauk, dotsent; STOROZHEV, V.V., aspirant

Design and calculation of shuttle systems and mechanisms for sewing machines. Nauch. trudy MTILP no.29:170-189 '64. (MIRA 18:4)

1. Kafedra mashin i apparatov Moskovskogo tekhnologicheskogo instituta legkoy promyshlennosti.

KOMISAROV, A.I., kand. tekhn. nauk, dots.; SHCHOCHEV, V.V., aspirant

[Shuttle systems and mechanisms of sewing machines; characteristics of design and operation, design and calculations] Chelnochnye ustroistva i mekhanizmy shveinykh mashin; osobennosti konstruktsii i raboty, proektirovanie i raschet. Moskva, Mosk. tekhnologicheskii in-t legkoi promyshl., 1964. 19 p. (MIRA 18:4)

STOROZHEV, V.V.; RACHOK, V.V.; KOMISSAROV, A.I.

Wear of rotating shuttles. Shvein.prom. no.5:23-25 S-O '65.
(MIRA 18:10)

[illegible] Animals - [illegible] Helminths.

Abs Jour : Ref Zhur - Biol., No 11, 195[illegible], 50840

Author : Storozhova, A.M.
Inst : -
Title : Physocephalosis in Domestic Hens, Ducks, and Geese.

Orig Pub : Veterinariya, 1957, No 10, 47-49.

Abstract : According to the author's data, the spiruratic larvae, which parasitize in hens, ducks and geese should be classified as Physocephalus semilatus Molin 1860. These larvae are localized on the walls of the esophagus and of the [illegible]ach, on the serous coatings of the musculo[illegible]ar [illegible]ach, in the pericardium, in the mesentery, and in the parenchymatous organs. Domestic fowl must be regarded as [illegible] only hosts, while pigs, rabbits, donkeys, horses, and large horned cattle are the actual hosts of the larvae. Pigs and transitory hosts are sources of physocephalosis infection of domestic birds. Measures to combat

Card 1/2

- 42 -

[redacted], A.I., kand. tekhn. nauk, dotsent; [redacted], V.V., assistent; [redacted], F.I., aspirant

Effect of the structure of thread interlacing on the quality of the shuttle stitch. Izv. vys. ucheb. zav.; tekh. tekst. no.2:198-204 '63. (MIRA 17:11)

1. Kafedra tkatskikh i apparatov Moskovskogo tekhnologicheskogo instituta legkoy promyshlennosti.

[illegible] A., [illegible] -- [illegible] "[illegible]
of [illegible] fowl in [illegible] [illegible] (Black [illegible]
[illegible] zone of the USSR and its [illegible]
[illegible]." [illegible], 1958, 11 [illegible] (All-[illegible] of
[illegible] Agr [illegible] V.I. Lenin. All-[illegible]
[illegible] V.I. [illegible]
[illegible] (KL, [illegible], 120)

STOROZHEVA, A.M., aspirant

Helminths of domestic water birds in Grodno Province in the White Russian Polesye from the point of view of their seasonal dynamics. Trudy VIGIS 6:177-182 '59. (MIRA 15:5)
(Parasites--Water birds)
(White Russia--Worms, Intestinal and parasitic)

PETYUNIN, P.A.; STOROZHEVA, A.V.

Phenylhydrazides of N-substituted oxamic acids. Zhur.ob.khim. 32 no.5:1395-1398 My '62. (MIRA 15:5)

1. Permskiy farmatsevticheskiy institut.
(Oxamic acid)

PETYUNIN, P.A.; STOROZHEVA, A.V.

Amides and hydrazides of oxalic acid. Part 2: Acyl derivatives of aryl hydrazides of N-substituted oxamic acids. Zhur.ob. khim. 33 no.2:400-405 F '62. (MIRA 16:2)

1. Permskiy farmatsevticheskiy institut.
(Oxamic acid) (Hydrazides)

STOROZHEVA, M.M.

Teratological phenomenon of the pasqueflower Pulsatilla Patens (L.) Mill. in a nickel ore field. Trudy Biogeokhim.lab. 10:64-75 '54. (Pasqueflowers) (Plants, Effect of metals on) (MLRA 8:7)

STOROZHEVA, M. M.

USSR Physiology of Plants

Card 1/1

Author : Storozheva, M. M.

Title : Effect of copper and boron in increasing the yield of feed grasses and resistance of clover to cold in the conditions of the Northern Trans-Ural regions.

Periodical : Dokl. AN SSSR, 95, 6, 1341 - 1342, 21 Apr 54

Abstract : The addition of copper and boron to soil fertilizers produces a quite conspicuous effect on the grass yield. The addition of copper increases the yield by about 84%; boron - 60%; a combined copper and boron mixture - 94%. Experiments performed on different varieties of clover by adding copper to a fertilizer showed that copper increases anti-frost stability of the clover.

Institution : Scientific Research Station of the Ural Branch of the Acad. of Scs. at Ivdel'sk.

Submitted : 25 Feb 54

STOROZHEVA, Mariya Mikhaylovna; GORCHAKOVSKIY, P.L., prof., doktor biolog.nauk, otv.red.; ARDASENOVA, L.P., red.izd-va; SEREDKINA, N.F., tekhn.red.

[Materials on the characteristics of bogs of the eastern slope of the Northern Urals and the Trans-Ural region] Materialy k kharakteristike bolot vostochnogo sklona Severnogo Urala i Zaural'ia. Sverdlovsk, 1960. 53 p. (Akademiia nauk SSSR. Ural'skii filial, Sverdlovsk. Institut biologii. Trudy, no. 20) (MIRA 14:2)

(Ural Mountain region--Peat bogs)
(Siberia, Western--Peat bogs)

STOROZHEVA, M.M.

Typology of swamps in the northern part of the trans-Ural region. Trudy Inst.biol.UFAN SSSR no.14:67-82 '60. (MIRA 14:6)
(Ural Mountain region--Swamps)

STOROZHEVA, M.M.

Age of the first terrace of the Kama Valley according to the data of the analysis of pollen in peat. Sbor. Sverd. otd. VBO no.2:115-123 '62. (MIRA 16:8)

STOROZHEVA, M.M.

Meadows of the river valleys of the Ivdel' region in the Urals. Trudy Inst.biol.UFAN SSSR. no.28:3-37 '62. (MIRA 16:1)
(Ivdel' region--Pastures and meadows)





PRITSKER, David Mikhaylovich, inzh.; TUR'YAN, Viktor Aleksandrovich, inzh.; STOROZHEVA, V.N., inzh., retsenzent; SAKHAROV, G.I., dotsent, kand.tekhn.nauk, retsenzent; KRASIL'NIKOV, S.D., inzh., red.; SHEYNFAYN, L.I., izdat.red.; GARNUKHINA, L.A., tekhn.red.

[Aeromechanics] Aeromekhanika. Moskva, Gos.nauchno-tekhn.izd-vo Oborongiz, 1960. 279 p. (MIRA 13:10)
(Aeronautics)

SUKHOVA, M.N.; YEROFEYEVA, T.V.; GVOZDEVA, I.V.; NIKIFOROVA, N.F.; LOTSENKO, T.K.; DEMYANCHENKO, E.I.; BIBALO, T.I.; SERAFIMOVA, A.M.; MOSUNOV, V.B.; SAMSONOVA, A.M.; SKOPOZHEVA, Ya.M.; SUPCHAKOV, A.V.

Methods of applying insecticides to control synanthropic flies. Zhur.mikrobiol., epid.i immun. 33 no.8:15-19 Ag '62. (MIRA 15:10)

1. Iz TSentral'nogo nauchno-issledovatel'skogo dezinfektsionnogo instituta Ministerstva zdravookhraneniya SSSR, Mytishchinskoy gorodskoy sanitarno-epidemiologicheskoy stantsii, Kuybyshevskogo instituta epidemiologii i mikrobiologii, Minskoy gorodskoy dezinfektsionnoy stantsii, Brestskoy sanitarno-epidemiologicheskoy stantsii, Tashkentskoy gorodskoy dezinfektsionnoy stantsii i Tashkentskoy gorodskoy sanitarno-epidemiologicheskoy stantsii.
(INSECTICIDES) (FLIES--EXTERMINATION)

[redacted]

[redacted]

[redacted]

[redacted]

[redacted]

SUKHOVA, M.N.; ZAIROV, K.S.; GVOZDEVA, I.V.; ANDREYEVA, A.I.; NURULLAYEV, D.Kh.; TALIPOV, M.Z.; MOSUNOV, V.B.; STOROZHEVA, Ye.M.; SAMSONOVA, A.M.; SHAMIRZAYEV, N.Yu.; AKMURZAYEV, T.A.

Fly control and its organization in Uzbekistan. Med.zhur.Uzb. no.3:3-14 Mr '62. (MIRA 15:12)

1. Iz TSentral'nogo nauchno-issledovatel'skogo dezinfektsionnogo instituta Ministerstva zdravookhraneniya SSSR (dir. - prof. V.I.Vashkov) i sanitarno-epidemiologicheskoy organizatsii Uzbekistana (glavnyy gosudarstvennyy sanitarnyy inspektor-kand.med.nauk K.S.Zairov).
(UZBEKISTAN--FLIES--EXTERMINATION)

L 22796-66 EWT(m)/EWP(w)/EWA(d)/T/EWP(t) IJP(c) JD/HW/GS

ACC NR: AT6000650 SOURCE CODE: UR/0000/65/000/000/0043/0048

AUTHORS: Storozhevskiy, I. M. (Kiev); Rudenko, V. N. (Kiev) 69 B+1

ORG: none

TITLE: Strength studies of metal-ceramic materials at low temperatures 18 14

SOURCE: Vsesoyuznoye soveshchaniye po voprosam staticheskoy i dinamicheskoy prochnosti materialov i konstruktsionnykh elementov pri vysokikh i nizkikh temperaturakh, 3d. Termoprochnost' materialov i konstruktsionnykh elementov (Thermal strength of materials and construction elements); materialy soveshchaniya. Kiev, Naukova dumka, 1965, 43-48

TOPIC TAGS: potentiometer, stress analysis, metal ceramic material, tensile test, test method, low temperature effect, metallurgic testing machine/ 1Kh18N9T steel, 1Kh18 9T steel, PP-1 potentiometer 16 18

ABSTRACT: Experiments are described for testing metal-ceramic materials in tension, compression, shear, and hardness at temperatures from 78 to 293K. The details of four testing facilities are outlined, one for a bending test at low temperatures, one for tension, one for shear, and one for compression. The test chambers in all four facilities are made of 1Kh18N9T stainless steel and are cooled by alcohol (down to 170K) and by liquid nitrogen (to 78K). Temperatures are measured with copper-constantan thermocouples and are monitored by a PP-1 potentiometer. Three sets of

Card 1/2

L 22996-66

ACC NR: AT6008650

O

porous iron metal samples were used as test specimens. The results show that the strength of the metal increases considerably as the temperature is lowered. The plastic characteristics of the same specimens, on the other hand, deteriorate, especially for the specimens with 5% porosity. Orig. art. has: 6 figures.

SUB CODE: 11, 13/ SUBM DATE: 19Aug65/ ORIG REF: 014/ OTH REF: 004

Card 2/2 pla

L 20963-66 EWP(e)/EWT(m)/EWP(k)/EWP(t) IJP(c) JD
ACCESSION NR: AP5013253 UR/0226/65/000/005/0063/0070

AUTHOR: Storozhevskiy, I.M.; Filatova, N.A.

TITLE: Investigation of the laws of change in tensile strength of some copper-based sintered materials

SOURCE: Poroshkovaya metallurgiya, no. 5, 1965, 63-70

TOPIC TAGS: tensile strength, powder metallurgy

ABSTRACT: Experimental data are presented on the tensile strength of porous copper-based sintered materials in the low-temperature region. In the investigated materials the strength rises by 38-60 percent over that observed at room temperature as the temperature falls from 293 to 78°K. With a fall in the testing temperature the ultimate strength varies according to a linear law, and with a decrease in porosity there is a marked dependence on the temperature. With low porosity values the ultimate strength at room temperature decreases by a linear law. The dependence is preserved at low temperatures. With a fall in temperature there is a sharper dependence of the strength on the porosity. Orig. art. has: 7 figures.

Card 1/2

L 20963-66
ACCESSION NR: AP5013253

ASSOCIATION: Institut problem materialovedeniya AN UkrSSR (Institute of Problems in the Science of Materials)

SUBMITTED: 23Jul64 ENCL: 00 SUB CODE: MM

NO REF SOV: 008 003

Card 2/2 mlp 5

[illegible], I.N.

Modeling a porous material and determining the relative reservoir of its cross section by porosities. Poroshk.met. 5 no.3 [illegible] 75 (MIRA 18:5)

1. Kirovogradskiy filial Khar'kovskogo politekhnicheskogo instituta imeni V.I.Lenina. Submitted March 14, 1965.

ACC NR: AP6017105 (N) SOURCE CODE: UR/0126/66/000/001/0062/0068

46
44
B

AUTHORS: Storozhovskiy, I. N.; Filatova, N. A.

ORG: Institute for Problems of Materials Behavior, AN UkrSSR (Institut problem materialovedeniya AN UkrSSR)

TITLE: Investigation of changes in the impact viscosity (resilience) of some sintered materials at low temperatures

SOURCE: Poroshkovaya metallurgiya, no. 1, 1966, 62-68

TOPIC TAGS: metal powder, powder alloy, powder metal compaction, ~~powder metallurgy~~ solid viscosity, sintered metal

ABSTRACT: The effect of temperature and degree of porosity on the resiliency and microstructure of Cu-Ni, Fe-Ni, Cu-Sn, and Sn-C sinters was investigated. The investigation supplements the results of I. N. Storozhovskiy and N. A. Filatova (Poroshkovaya metallurgiya, No. 6, 1965). The experimental procedure followed is described by I. G. Bondik (Mekhanicheskiye ispytaniya metallov, Izd-vo AN UkrSSR, K., 1962). The experimental results are summarized in graphs and tables (see Fig. 1). The temperature dependence of the resiliency of the sintered materials investigated was similar in nature to that observed on cast materials. It was also found that the minimum in the resilience-temperature curve becomes less pronounced with increase in porosity of the sinter. It is concluded that the upper brittleness boundary for

Card 1/2

ACC NR: AP6017105

2

Fig. 1. Temperature dependence of impact viscosity (resilience) of copper-nickel material. 1 - cast material (R. E. Lismor. J. Inst. Metals, January, vol. 89, Pt. 5, 1961, pp. 145--161); 2, 3, 4 - metal sintered material.



Fe-Ni, bronze, and bronze-graphite containing 3% graphite lies at about 230K, and for Cu-Ni at approximately 123K, whereas the sinter composed of bronze + 5% boron nitride remains brittle over the whole temperature range investigated. Orig. art. has: 1 table and 4 graphs.

SUB CODE: 11/ SUBM DATE: 25Apr65/ ORIG REF: 010/ OTH REF: 005

Card 2/2 gd

L 44[illegible] EWT(m)/EWP(k)/EWP(e)/EWP(t)/ETI IJP(c) ES/JD

ACC NR: AP6007289 SOURCE CODE: UR/0226/66/000/002/0063/0068

AUTHOR: Storozhevskiy, I. M.; Filatova, N. A.

ORG: Institute for the Study of Materials, AN UkrSSR (Institut problem materialovedeniya AN UkrSSR)

TITLE: Bending strength of iron- and copper-base powdered-metal materials in the low--temperature region

SOURCE: Poroshkovaya metallurgiya, no. 2, 1966, 63-68

TOPIC TAGS: tensile testing machine, powder alloy, bending strength, porosity, temperature dependence / GM-250 (East German) tensile testing machine

ABSTRACT: This is a continuation of a previous investigation (I. M. Storozhevskiy, N. A. Filatova. Poroshkovaya metallurgiya, no. 5, 1965) with the difference that it deals with testing copper- and iron-base powdered-metal materials in order to confirm the universality of the previous finding that the dependence of strength on porosity becomes more distinct with decreasing test temperature. To this end, mixtures of the powders of Fe, Cu and Ni were sintered and, in order to obtain varying porosities, compression-molded under various pres-

Card 1/2

ACC NR: AP6007289

sures. Fe specimens were sintered in a hydrogen atmosphere for 2 hr at 1473°K, while Fe + 10% Ni and Cu + 10% Ni alloys were sintered in a hydrogen atmosphere for 8 hr at 1473 and 1273°K, respectively. After this, the specimens were tested in a GM-250 (East German) tensile testing machine at 78, 175, 230 and 293°K. Findings: when the temperature is reduced from 293 to 78°K the strength of the investigated materials increases by 145-330% compared with their strength at room temperature. Low temperatures affect more sharply the materials with low porosity. The curvilinear dependence of strength on temperature for low porosities (10-12%) gets gradually transformed into a linear dependence with increase in porosity (to 40-50%). The sharper temperature dependence of strength for materials with low porosities is apparently a general rule that applies to various plastic materials prepared by methods of powder metallurgy. In this connection, the authors propose a method of predicting the effect of porosity on strength at various temperatures with the aid of the dimensionless coordinates σ and η, where σ is the ratio of the investigated property of a material at a given test temperature and porosity to the same property at the same porosity but at a test temperature taken as the base temperature (e.g. room temperature (293°K)), and η is porosity. Orig. art. has: 6 figures.

SUB CODE: 11, 13, 20/ SUBM DATE: 26Aug65/ ORIG REF: 006/ OTH REF: 002/

Card 2/2 hs

L 26592-66 EWT(m)/EWP(e)/EWP(w)/T/EWP(t)/EWP(k) IJP(c) JD

ACC NR: AP6011352 SOURCE CODE: UR/0226/66/000/003/0096/0100

AUTHORS: Rudenko, V. N.; Storozhevskiy, I. M.

ORG: Institute for Materials Behavior Problems, AN UkrSSR (Institut problem materialovedeniya AN UkrSSR)

TITLE: Investigation of the strength and plasticity of sintered iron during tension in the low-temperature region

SOURCE: Poroshkovaya metallurgiya, no. 3, 1966, 96-100

TOPIC TAGS: iron, iron powder, powder metal, powder metallurgy/ PZhlM1 iron powder

ABSTRACT: The effect of porosity and temperature on the strength and plastic properties of sintered iron was investigated. The work supplements the results obtained by A. Ya. Krasovskiy (Poroshkovaya metallurgiya, No. 4, 1, 1964). The specimens were prepared from PZhlM1 iron powder, and their tensile strength and plasticity were determined in the temperature range of 77--293K. The experimental results are shown graphically (see Fig. 1). These results are compared with literature data. The effect of porosity on the strength limit at different temperatures is shown in terms of the dimensionless parameters ρ and η

$$\rho_{\sigma_b} = \frac{(\sigma_b)_T}{(\sigma_b)_{293^\circ}}$$

Card 1/2

L 26592-66

ACC NR: AP6011352



Fig. 1. Effect of porosity on the strength limit of sintered iron at various temperatures.

where $(\sigma_b)_T$ and $(\sigma_b)_{293}$ are the strength limits of the material of given porosity at the temperature T and at 293K respectively. It is concluded that low temperatures have more effect on the strength of iron, the greater porosity of the latter. Orig. art. has: 5 graphs.

SUB CODE: 11,20/ SUBM DATE: 11Jun65/ ORIG REF: 014/ OTH REF: 003

Card 2/2 BLG

L 46303-66 EWT(m)/EWP(t)/ETI IJP(c) JD/WW/HM

ACC NR: AP6025940 SOURCE CODE: UR/0226/66/000/007/0069/0072

AUTHOR: Storozhevskiy, I. M.; Filatova, N. A. 69 C

ORG: Institute of Problems in the Science of Materials, AN UkrSSR (Institut problem materialovedeniya AN UkrSSR)

TITLE: Strength and ductility of cermet materials at low temperatures

SOURCE: Poroshkovaya metallurgiya, no. 7, 1966, 69-72

TOPIC TAGS: cermet, ductility, fatigue strength, fatigue test, porosity, iron nickel alloy, bronze, mechanical property, LOW TEMPERATURE EFFECT

ABSTRACT: This is a continuation of previous studies by the authors and others. Tensile strength and relative contraction and elongation after destruction were studied as functions of porosity on iron-nickel, bronze and graphitized bronze cermet specimens at 78, 175, 230 and 293°K. 4-5 specimens were used for each test stage and the results were averaged. It is shown that strength is a curvilinear function of porosity throughout the experimental temperature range, with a more pronounced dependence at low temperatures. Ductility is also a nonlinear function of porosity at all temperatures. This relationship is not as strong for iron-nickel and graphitized bronze as it is for bronze. Ductility as a function of porosity for bronze increases as temperature is reduced to 230°K. Any further reduction in temperature past this

Card 1/2

L 46303-66

ACC NR: AP6025940

point reestablishes the characteristic relationships which hold for iron-nickel and graphitized bronze. The strength of the given materials increases by 120-180% as temperature is increased. If porosity values are low, strength as a function of temperature becomes curvilinear. As porosity increases, curvilinearity decreases and at large porosity values the function approaches a straight line. Ductility does not vary uniformly for all materials as temperature is decreased. Bronze contracts as the temperature is reduced to 230°K and expands below this temperature. Iron-nickel and graphitized bronze show a reduction in ductility as temperature is decreased. This is more pronounced for low-porosity materials. Orig. art. has: 3 figures.

SUB CODE: 11, 13/ SUBM DATE: 12Oct65/ ORIG REF: 006

Card 2/2 ULR

STOROZHIK, A.O.

Multiplace vices. Stan. i instr. 24 no.5:31-32 My '53. (MLRA 6:6)
(Machine tools)

USSR/Miscellaneous - Machining

Card : 1/1

Authors : Storozhik, A. G.

Title : Machining segments of tubing (parts of large tubes) on milling machines.

Periodical : Stan i instr., 3, 29 - 30, Mar 1954

Abstract : Machining surfaces of large tunnel faceplates on horizontal milling machines, with newly designed cutter heads held in place by a new method is described.

Institution : ....

Submitted : ....

STOROZHIK, A.G.

Hollow drills for cast iron drilling. Stan. i instr. 26 no.12: 32-33 D '55. (MLRA 9:2)
(Drilling and boring machinery)

AID P - 4862

Subject : USSR/Engineering

Card 1/1 Pub. 103 - 22/26

Author : Storozhik, A. G.

Title : Composite cutter

Periodical : Stan. i instr., 2, 42, F 1956

Abstract : This cutter is provided with a head-stock into which a special insert is fastened. Designed by F. I.Poddubnyak and tried on a large roll-lathe, it was found that less time was required to replace the head-stock with a dulled cutting edge than to install the whole cutter. Two drawings.

Institution : None

Submitted : No date

AID P - 5174

Subject : USSR/Engineering

Card 1/1 Pub. 103 - 15/19

Authors : Podvorchanskiy, Ye. M., A. G. Storozhik and D. A. Storozhik.

Title : Sectional - assembled milling cutters for machining specimens of complicated shape.

Periodical : Stan. i instr., 6, 43-44, Je 1956

Abstract : The authors describe a sectional milling cutter developed by them for machining parts of various profiles and complicated shapes with a use of a copying device. Three diagrams.

Institution : None

Submitted : No date

STOROZHIK, A.G.

Composite cutting tool. Stan. i instr.27 no.2:42 F '56. (MLRA 9:7)
(Cutting tools)

AUTHOR: Storozhik, A.G. 121-4-28/32

TITLE: The Manufacture of Taps with Interrupted Thread (Izgotovleniye metchikov s preryvistoy rez'boy)

PERIODICAL: Stanki i Instrument, 1958, No.4, p.41 (USSR).

ABSTRACT: The cutting of every other thread between two neighbouring flutes in a chessboard pattern is carried out with a profiled grinding wheel after heat treatment and finish profile grinding. Such taps yield smoother tapping, especially in steel castings.

There are 2 figures.

AVAILABLE: Library of Congress

Card 1/1

1. Taps-Production methods

STOROZHIK, A.O.

Spiral double-tooth reamers. Stan. i instr. 30 no.2:39 F '59.
(MIRA 12:3)

(Reamers)

STOROZHIK, A.G.

Drill for boring holes in organic glass. Stan.i instr. 30 no.3:33 Mr '59. (MIRA 12:3)
(Drilling and boring machinery)

STUKOZHIK, A.G.; MATYASH, A. Ye.

Continuous running machine for lapping cutters. Stan. i instr. 31 no.5:33-34 My '60. (MIRA 14:5)
(Grinding machines)

[redacted]

[redacted]

STOROZHIK, D.A., inzhener.

Hydraulic packing for charge distributors operated under high pressures. Stal' 16 no.4:367-368 Ap '56. (MLRA 9:7)

1.Zavod "Zaporozhstal'".
(Blast furnaces)

AID P - 5174

Subject : USSR/Engineering

Card 1/1 Pub. 103 - 15/19

Authors : Podvorchanskiy, Ye. M., A. G. Storozhik and D. A. Storozhik.

Title : Sectional - assembled milling cutters for machining specimens of complicated shape.

Periodical : Stan. i instr., 6, 43-44, Je 1956

Abstract : The authors describe a sectional milling cutter developed by them for machining parts of various profiles and complicated shapes with a use of a copying device. Three diagrams.

Institution : None

Submitted : No date

STOROZHIK, D.A., inzhener.

Replacement of rapidly wearing skip hoist parts. Metallurg no.8:6-9 Ag '56. (MLRA 9:10)

1.Master-mechanik domennogo tsekha zavoda "Zaporozhstal'."
(Hoisting machinery)

STOROZHIK, D.A.

Changing the double stuffing-box packing. Metallurg 2 no.1:9-10 Ja '57. (MLRA 10:4)

1. Master-mekhanik domennogo tsekha zavoda "Zaporozhstal'".
(Blast furnaces)

AUTHOR: Storozhik, D. A.

TITLE: Blast Furnace Equalising Valves. (Uravnitel'nyye Klapany Domennoy Pechi).

PERIODICAL: Stal', 1957, No.10, pp. 874-882 (USSR).

ABSTRACT: Types of equalising valves (I - "butterfly" with a cable drive, II - with a built in electric drive, III - double valves with a built in electric drive) for high top pressure operation used on the Zaporostal' Works, their operating practice and maintenance requirements are described and illustrated in diagrams. On the basis of experience the third type - double valves with a built in electric drive is recommended for new furnaces. These were designed by K. P. Gulyanitskiy, A. I. Dinamov and N. I. Nizozemtsev . There are 7 figures.

ASSOCIATION: Zavod "Zaporozhstal'" ("Zaporozhstal'" Plant)

AVAILABLE: Library of Congress

Card 1/1

Sov/133/58-9-27/29

AUTHORS: Skienko, P. Ya., Onishchenko, P.I. and Storozhik, D. A. (Engineers)

TITLE: Experience of Operation of a Tower Type Wagon Tippler (Opyt raboty bashennogo vagonoprokidyvatelya)

PERIODICAL: Stal', 1958, Nr 9, pp 852-858 (USSR)

ABSTRACT: A description of the wagon tippler of Soviet design which operated for a number of years at the Zaporozhstal' Works is outlined and illustrated. Modifications made during the trial period as well as some proposed design changes are described. There are 9 figures and 1 table.

ASSOCIATION: Institut chernoy metallurgii AN SSSR i zavod "Zaporozhstal'" (Institut for Ferrous Metallurgy, AS USSR, and the "Zaporozhstal'" Plant)

Card 1/1

AUTHOR: Stepchak, D. A. ( )

TITLE: Concerning the [illegible] of Valve Ports With Flow of Solid Suspension as Used in Blast Furnaces

PERIODICAL: Izvestiya vysshikh [illegible], Chernaya metallurgiya, [illegible] (USSR)

ABSTRACT: The insufficient [illegible] of contact surfaces of blast furnace valve [illegible] during work with increased gas pressure under the top of the furnace, is explained by the [illegible] geometric shape and existing [illegible] of locking valve parts (see Fig. 1). Although [illegible] of manufacture of such parts is high, the assembly is unsatisfactory. All parts are [illegible] in bases with 15 to 20 mm asbestos [illegible], which results in a nonuniform tightness. [illegible] of matching of the large bell, [illegible] to 5 mm. The

Card 1/10

Concerning the Stresses and Thrust
of Valve Parts With Free or Blast
Suspension as Used in Blast Furnace

experience of [illegible] the thickness
of the large bell [illegible] due to poor contact
of the bell with [illegible] caused by the
large bell being [illegible] by the gas flow,
a nonuniform distribution [illegible] on the bell
surface, inaccurate [illegible], tilting, wear, etc.
If the amplitude of [illegible], the bell can
touch the seat in [illegible] thus contacting
the seat only in two diametrically opposed points
with a clearance along the [illegible] surface be-
tween these points (see Fig.). In giving a
mathematical analysis [illegible] for the case
of a large bell and hopper [illegible] were made
by I. S. Belak), [illegible] simplifications
for the case of the [illegible] the following
conclusions and [illegible]: It is possible
to eliminate the [illegible] of the large bell
by making the [illegible] of the bell spherical

Card 2/10

and that of the hopper either tapered (see Fig. 8) or also spherical. The latter was suggested by N. K. Borodenchik, A. I. Dikalov, and D. A. Storozhik.



Fig. 1. Valve with tapered seat and hinged joint of the mobile part with the arm (an incorrect design).

Concerning the Skewness and Tightness of Valve Parts With Free or Elastic Suspension as Used in Blast Furnaces



Fig. 8. Schematic diagram of the large bell with spherical contact surface.

Card 4/10

Concerning the Stresses and Tightness of Valve Parts With Face or Ridge Suspension as Used in Blast Furnaces

TITLE
SOV/148-59-9-19/22

In the case of a tapered seat the high specific pressures on a narrow contact surface cause compression and wear of about 2 mm wide contact surface. In this case the cone must be hand-faced while the seat remains soft. With a spherical ball contact it is possible to obtain any working force depending on the selected height of the center of the spherical surface. The spherical ball surface should be made with an angle $\alpha > 90^{\circ}$ (as shown in Fig. 8) which prevents the spherical surface from abrasion by the stream. With a spherical surface

Card 5/10

Fig. 2. Schematic diagram for determining the angle of tilting of the large bell. R_r, R_c are total reactions at supports without consideration of friction forces; r is minimal radius of the hopper; n is deviation of the joint of the rod with the bell from the axis of the hopper; h is height of contact surface of the hopper, in cm; Q = 20,000 kg, i.e., weight of large bell unit; m = 210 cm, distance from the center of gravity of the bell unit to the vertex of the bell cone; T is force of gas pressure on the bell (with nonuniform gas pressure); El = $10.35 \cdot 10^9$ kg/cm^2, rigidity of the bell rod; P is force acting on the rod, equals 75,000 kg; L = 1650 cm, distance from the vertex of the bell cone to the middle joint of the rod; l = 1,500 cm, distance from the lower bushing of the small bell rod to the first joint of the rod; P_1 is horizontal force in the rod at tilted

position of the ball (in the plane of imaginary intersection); M is elastic moment in the rod (in the plane of imaginary intersection); ρ is angle of repose (tan ρ = f, coefficient of friction); φ is maximal angle of tilting.

of the large ball, the high precision of its centering ($\pm$ 1.5 mm) is not required. The universal joint, which is theoretically needed for joining the large ball to its rod, is also superfluous since, due to the low rigidity of the rod the latter will bend and play the role of hinged suspension. The suggested design of the valve with spherical seat and joint is shown in Fig. 9.

Card 8/10

Concerning the Strength and Tightness of Valve Seats With Face or Elastic Suspension as Used in Blast Furnaces

SOV/148-58-9-19/23



Fig. 9. Valve with a spherical seat and spherical joint of the mobile part with the arm.

Card 9/10

Concerning the Sturdiness and Tightness of Valve Parts With Free or Elastic Suspension, as Used in Blast Furnaces

7714
SOV/148-59-9-19/22

The centers of both spheres, i.e., of contact and of the joint must be located at a maximum possible distance from each other and should never coincide. Such valve design proved to be satisfactory in practice. There are 3 figures; and 4 references, 3 Soviet, 1 U.S. The U.S. reference is: Fawcett, F., Iron and Steel Engineer, Nr 1, 55 (1950).

ASSOCIATION: Dnepropetrovsk Metallurgical Institute (Dnepropetrovskiy metallurgicheskiy institut)

SUBMITTED: July 15, 1959

Card 10/10

DOBROV, V.P.; KVASHA, A.N.; STOROZHIK, D.A.

Calculating the strength of bell hoppers of the blast furnace charging apparatus. Izv. vys. ucheb. zav.; chern. met no.8:167-180 '60. (MIRA 13:9)

1. Dnepropetrovskiy metallurgicheskiy institut.
(Blast furnaces)

BORODENCHIK, N.K.; DIKALOV, A.I.; STOROZHIK, D.A., KIMARA, A.M.

Three-bell charging hopper. Metallurg 6 no.2:7-11 F '61.
(MIRA 14:1)

1. Zavod "Zaporozhstal'" i Dnepropetrovskiy metallurgicheskiy institut.
(Blast furnaces—Design and construction)

DOROLENCHIK, N.K.; DIKALOV, A.I.; STOROZHIK, D.A.

Increasing the durability of blast furnace charging equipment. Stal' 21 no.9:782-790 S '61. (MIRA 14:9)

1. Zavod "Zaporozhstal'" i Dnepropetrovskiy metallurgicheskiy institut.

(Blast furnaces—Equipment and supplies)

STOROZHIK, D.A.

Ways of increasing the flexibility of blast furnace charging hoppers. Izv.vys.ucheb.zav.; chern.met. 5 no.6:175-181 '62.
(MIRA 15:7)

1. Dnepropetrovskiy metallurgicheskiy institut.
(Blast furnaces—Equipment and supplies)

KLYUCHNIK, V.K.; TSERLYUK, A.L.; STOROZHIK, D.A.; LEONOVA, A.V.

Standardizing blast furnace charging equipment. Met. i gornorud. prom. no.3:14-16 My-Je '63. (MIRA 17:1)

1. Dnepropetrovskiy proyektno-konstruktorskiy tekhnologicheskiy institut (for Klyuchnik, TSerlyuk). 2. Dnepropetrovskiy metallurgicheskiy institut (for Storozhik, Leonova).

STOROZHIK, D.A.

Preventing the wear of the generatrix of large bells in blast furnaces. Izv. vys. ucheb. zav.; chern. met. 6 no.10:173-180 '63. (MIRA 16:12)

1. Dnepropetrovskiy metallurgicheskiy institut.

DIKALOV, A.I.; LEONOVA, A.V.; STOROZHIK, D.A.

New design of the charge distributer. Metallurg 8 no.8:9-11 Ag '63. (MIRA 16:10)

1. Zaporozhskiy staleplavil'nyy zavod "Zaporozhstal'" i Dnepropetrovskiy metallurgicheskiy institut.

DAKALOV, A.I.; LEONOVA, A.V.; STOROZHIK, D.A.

Increasing the durability of the charging equipment. Metallurg 8 no.10:10-12 O '63. (MIRA 16:12)

1. Zavod "Zaporozhstal'", i Dnepropetrovskiy metallurgicheskiy institut.

GREBENIK, V. M.; LEONOVA, A. V.; STOROZHIK, D. A.; NECHIPORENKO, V. N.

Investigating regularities of the gas flow and the wear of coupled parts in blast furnace charging arrangements. Izv.vys.ucheb.zav.; chern.met. 7 no. 4:182-185 '64. (MIRA 17:5)

1. Dnepropetrovskiy metallurgicheskiy institut.

[redacted], V.I., [redacted], S.B., SHEVLYAKOV, V.G., [redacted], I.A.

[redacted] of the mechanical equipment of blast furnaces with [redacted] 'Stal' 24 no.10:871-874 O '64.
(MIRA 17:12)

GEORGIYENKO, V.L.; STOROZHUK, E.A.; USACHEV, V.P.

Using electromagnetic vibrating screens for the sieving of coke breeze.
Metallurg 10 no.9:3-5 S '65. (MIRA 18:9)

80(0)

3.5000 SOV/124-59-9-10392

Translation from: Referativnyy zhurnal, Mekhanika, 1959, Nr 9, p 113 (USSR)

AUTHORS: Vlasenko, G.Ya., Deryagin, B.V., Kudryavtseva, N.M., [illegible] V.V., Storozhilova, A.I., [illegible]

TITLE: Flow Methods for Investigating Atmospheric Aerosols

PERIODICAL: V sb.: Issled. oblakov, osadkov i grozovogo elektrichestva Leningrad, Gidrometeoizdat, 1957, pp 1[illegible] - 1[illegible]

ABSTRACT: Not only the number of particles within the volume unit, but also their dimension distribution can be determined by the ultramicroscopic flow investigating method. For this purpose, an optical discriminator (photometric wedge), making it possible to obtain the particle-brightness distribution, was mounted into the target illuminating device of an ultramicroscope. A new wedge-graduation method is described. The graduation curves of the dependence of particle dimensions on the wedge position can be obtained quickly, when applying the method mentioned. The authors report on the flow method applied to the study of the atmospheric condensation nuclei. For this purpose, a single

Card 1/2

80(0)

SOV/124-59-9-10392

Flow Methods for Investigating Atmospheric Aerosols

accessory device is developed for "revealing" the condensation nuclei containing in the atmosphere. This accessory device consists of an air-moistening chamber and a cooling channel, in which vapor condensation on the condensation nuclei proceeds. The condensation nuclei, enlarged in this way, are carried away by the air current, arrive at the cell of the ultramicroscope, and can be recorded by the observer. The optimum operation conditions of the device were determined experimentally. By the ultramicroscopic flow method, the automation of registering aerosol particles or "revealed" condensation nuclei can be brought about. The design of an automatic counter developed for this purpose is presented. This [illegible] carries out the registration of aerosol particles of high [illegible] concentration without failing.

B.V. Deryagin

Card 2/2

STOROZHILOVA, A. I.

"Flow method of the study of the origin and movement of aerosol particles
To be presented at the First National Conference on Aerosols -
Liblice, Czechoslovakia, 8-13 Oct 1962

[illegible], B.V.; [illegible]

Thermophoresis of aerosol particles in laminar flow by the jet method. Koll. zhur. [illegible] no.5:587-592 S-O '64. (MIRA 17:10)

1. Institut fizicheskoy khimii AN SSSR, Moskva.

L 4952-66 ENT(1)/ENA(j)/ENA(b)-2 JK

ACC NR: AP5025713 SOURCE CODE: UR/0286/65/000/018/0067/0067

AUTHOR: Storozhilova, A. I. 55

ORG: none

TITLE: Method for collecting microorganisms from air. Class 30, No. 174766

SOURCE: Byulleten' izobreteniy i tovarnykh znakov, no. 18, 1965, 67

TOPIC TAGS: microorganism, aerosol, microorganism collection

ABSTRACT: This Author Certificate presents a method for collecting microorganisms from air by gathering them on a nutritional medium. To increase the effectiveness of collecting, the stream of particles to be precipitated is introduced into a laminar flow of moist air. The latter is directed through a channel with sterile walls. The temperature along the channel is varied to cause supersaturation of the water vapor. This in turn leads to the precipitation of the particles of interest.

SUB CODE: LS/ SUBM DATE: 16Mar64

Card 1/1 UDC: 614.71:542.953:576.8.093

STOROZHINSKIY, Anatoliy Ivanovich, inzh., SERDYUK, O.F., red.; PATVEYCHUK, A.A., tekhn. red

[Results of the observations of the Odessa Magnetic Observatory for 1960] Rezul'taty nabliudenii Odesskoi magnitnoi observatorii za 1960 g. Kiev, Izd-vo AN Ukr. SSR, 1963. 122 p. (MIRA 16:11)

1. Rukovoditel' Odesskoy magnitnoy observatorii (for Storozhinskiy).
(Odessa region--Magnetism, Terrestrial--Observations)

137-58-5-8781

Translation from: Referativnyy zhurnal, Metallurgiya, 1958, Nr 5, p 7 (USSR)

AUTHORS: Nekhay, S. M., Storozhko, A. I.

TITLE: An Investigation of Briquetting Operations Performed on Copper Ores (Issledovaniye briketirovaniya mednykh rud)

PERIODICAL: Byul. tsvetn. metallurgii, 1957, Nr 16, p 26

ABSTRACT: In order to determine optimal pressures for the making of briquets of maximum strength, investigations of briquetting operations on Cu ores were performed at the Dnepropetrovsk plant for medium hydraulic and heavy mechanical presses. It was found that specific pressures amounting to 1800 kg/cm^2 produce briquets of greatest strength.

A. Sh

1. Copper ores--Processing

Card 1/1

Measurement of the rate of motion of aerosol particles in the field of steam diffusion. Dokl. AN SSSR 155 no. 2:426-429 Mr '64. (MIRA 17:5)

1. Institut fizicheskoy khimii AN SSSR. Predstavleno akademikom M. M. Dubininym.

STOROZHKO, I.

Creative plans of society members. NTO 3 no.6: 40-42 Je '61.
(MIRA 14:6)

1. Predsedatel' soveta nauchno-tekhnicheskogo obshchestva Gor'kovskogo avtozavoda, zamestitel' glavnogo inzhenera.
(Gorkiy--Automobile industry)

KISELEV, I.I.; BORISOV, N.I.; YASINOVSKIY, B.S., inzh.; SANNIKOV, Yu.K., inzh.; SOKOLOV, V.A., inzh.; LEVCHENKO, L.D., inzh.; MALOYEV, G.A., inzh.; CHICHAKOV, K.K., inzh.; BARYKIN, V.I., inzh.; FREYDLIN, A.Ya., inzh. GULYAYEV, A.I., inzh.; STIGNEYEV, Ya.F., inzh.; SHAGANOVA, K.N., inzh.; KHELIMSKIY, I.Ye., inzh.; AVROV, A.N., inzh.; DEMIDOVA, M.I., inzh.; NIKIFOROVA, Ye.D., inzh.; KLIBANOVA, F.I., inzh.; CHIVKUNOV, K.I., inzh.; STOROZHKO, I.G., inzh.; NOVAKOVSKIY, Ye.Ya., inzh.; GOYKHTUL', A.O., inzh.; TARASOV, A.M., inzh.; SHISHKO, A.P., inzh.; UVAROV, P.T., ekonomist; DRAGUNOV, M.V., ekonomist; KARANDASHOV, A.A., ekonomist; KOMKIN, M.V., ekonomist; GOREV, M.S., ekonomist. Prinimali uchastiye: LAPIN, T.I.; RAMENSKIY, Yu.A.; KADINSKIY, B.A.; SOKOLOV, S.D.; STOROZHKO, I.G.; POMINYKH, A.I., POLYAKOVA, N., red.; SMIRNOV, G., tekhn.red.

[Organization and improvement of production; practices of the Gorkiy Automobile Plant] Organizatsiia i sovershenstvovanie proizvodstva; opyt Gor'kovskogo avtozavoda. Moskva, Gos. izd-vo polit. lit-ry, 1958. 332 p. (MIRA 12:2)

1. Direktor Gor'kovskogo avtomobil'nogo zavoda (for Kiselev).
2. Glavnyy inzhener Gor'kovskogo avtomobil'nogo zavoda (for Borisov).
3. Gor'kovskiy avtomobil'nyy zavod (for all except Kiselev, Borisov, Polyakova, Smirnov).

(Gorkiy--Automobile industry)

L 23425-66 EWT(1)/FCC GW

ACC NR: AT6012596 SOURCE CODE: UR/3201/65/000/002/0099/0107

16

AUTHOR: Storozhko, V. S. B+1

ORG: Institute of Applied Geophysics (Institut prikladnoy geofiziki)

TITLE: Problems of checking the apparatus of the automatic meteorological measurements of the units at the high tower of the Institute of Applied Geophysics

SOURCE: Leningrad. Institut prikladnoy geofiziki. Trudy, no. 2, 1965. Pogranichnyy sloy atmosfery (Boundary layer of the atmosphere), 99-107

TOPIC TAGS: micrometeorology, meteorological tower, meteorological instrument, instrument calibration, lapse rate recorder, anemograph, bivane

ABSTRACT: Since the automatic instruments used at the 300-m meteorological tower and the conditions under which they operate differ from those existing at standard meteorological network stations, special calibration systems have been developed for checking, investigating, and adjusting the tower's instruments. A description is given of the [illegible] level and over a 2-year period to test the lapse-rate recorder [illegible], the [illegible] anemograph (FPA), and the bivane [illegible]. The [illegible] calibration of the TO re- [illegible]

Card 1/2 UDC: 551.576+505+508.2+508.5+510

I 22425-66
ACC NR: AT6012596

C

The dependence of the number of pulses per light flash delivered on flow rate, and [illegible] of the oscillograph recordings under the working conditions at the tower. The [illegible] investigation included calibration of the sensor against a master meter and checking the orientation of the sensor for specific azimuths under the tower's working conditions. Orig. art. has: 4 figures and 3 tables. [ER]

SUB CODE: 04/ SUBM DATE: none/ ORIG REF: 007/ ATD PRESS: 4233

Card 2/2

STOROZHUK, A. (Kiyev); ZIMOVETS, V. (Kiyev)

Concentration of production and its effect on labor productivity and costs on collective farms. Vop. ekon. no.3:146-154 Mr '62. (MIRA 15:3)
(Khmel'nitskiy Province—Collective farms--Management)

BLOK, L.A.; STYROZHUK, [illegible]

Temperature measurements in a glass furnace. Stek. i ker. 20 no.9:35-36 S '63. (MIRA 17:6)

RAYGORODSKIY, G.D., inzhener; STOROZHUK, K.S., inzhener; UGOL'NIKOV, V.P., inzhener.

Establishing a feed water system at an electric power plant with high-pressure boilers. Elek.sta. 25 no.3:16-18 Mr '54. (MLRA 7:6)
(Feed water)

KOVCHAVTSEV, P.G., inzh; KOSTRYGIN, V.A., inzh.; STOROZHUK, K.S., inzh.

Reconstruction of RVS-110 valve-type discharger. Elek. sta. 30 no.2:65-66 F '59. (MIRA 12:3)
(Electric power distribution--Equipment and supplies)

KRYSHTAL', A.F., redaktor vypuska; STOROZHUK, L.F., redaktor; KHOKHANOVSKAYA, T.I., tekhnicheskiy redaktor

[Abstracts of reports at the Third Ecological Conference] Tret'ya ekologicheskaya konferentsiia. Tezisy dokladov. [Kiev] Izd-vo Kievskogo gos. univ. im. T.G.Shevchenko. Pt.4. 1954. 456 p. (MLRA 9:12)

1. Ekologicheskaya konferentsiya, 3rd, 1954. 2. Kiyevskiy gosudarstvennyy universitet (for Kryshtal')
(Ecology)

ZY[illegible], Viktor Maurovich; STORCZHUK, O.O.; LUTSO, A.Ya., red.; [illegible], O.I.[Rulenko, O.I.], tekhn. red.

[Production concentration on collective farms and its economic efficiency] Kontsentratsiia vyrobnytstva v kolhospakh i ii ekonomichna efektyvnist'. Kyiv, Derzhsil'-hospvydav URSR, 1962. [illegible] p. (MIRA 16:12)
(Ukraine--Collective farms--Management)

STOROZHUK, P.G.

Effect of Semigor'ye mineral water on gastric secretion in dogs. Vop. kur., fizioter. i lech. fiz. kul't. 26 no.6:498-503 N-D '61. (MIRA 15:1)

1. Iz sanatoriya "Goryachiy Klyuch" No.1 (glavnyy vrach G.T.Baste) i kafedry biologicheskoy khimii Kubanskogo meditsinskogo instituta (zav. - prof. N.P.Pyatnitskiy).
(SEMIGOR'YE--MINERAL WATERS--PHYSIOLOGICAL EFFECT)
(STOMACH--SECRETIONS)



APPROVED FOR RELEASE: 08/26/2000 CIA-RDP86-00513R001653410017-3"

[illegible], P.G.

Effect of Semigor'ye mineral water on the exocrine function of the pancreas in dogs. Vop. kur., fizioter. i lech. fiz. kult', 30 no.3:246-251 My-Je '65. (MIRA 18:12)

1. Kafedra biologicheskoy khimii Kubanskogo meditsinskogo instituta (zav. - prof. N.F. Pyatnitskiy), Krasnodar. Submitted September 15, 1964.

STOROZHUK, V.M.

Potentials at different levels of the cortical motor zone of a cat in a state of rest. Fiziol. zhur. [Ukr.] 7 no.4:482-489 Jl-Ag '61. (MIRA 14:7)

1. Electrophysiology Laboratory of the A.A.Bogomoletz Institute of Physiology of the Academy of Sciences of the Ukrainian S.S.R., Kiyev.
(ELECTROENCEPHALOGRAPHY)

STOROZHUK, V.A.

Evoked potentials at various levels of the motor zone of the cortex of a cat and their relation to electroencephalogram waves. Fiziol. zhur. [Ukr.] 8 no.1:100-106 Ja-F '62. (MIRA 15:2)

1. Laboratoriya elektrofiziologii Instituta fiziologii im. A.A.Bogomol'tsa AN USSR, Kiyev.
(ELECTROENCEPHALOGRAPHY)

STOROZHUK, V.M.

Electric potentials of various levels of the motor zone of the cortex in cats during a state of rest. Fiziol. zhur. [Ukr.] 8 no.2:193-197 Mr-Ap '62. (MIRA 15:5)

1. Laboratory of Electrophysiology of the A.A.Bogomoletz Institute of Physiology of the Academy of Sciences of the Ukrainian S.S.R., Kiev.
(ELECTROPHYSIOLOGY) (CEREBRAL CORTEX)